

Certificate of Conformity

Certificate Number: CN-PV-230654

On the basis of the tests undertaken, the sample<s> of the below product have been found to comply with the requirements of the referenced specification<s>/standard<s> at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture(s). The manufacture(s) shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant:	NINGBO AUSTA SOLAR TECH CO., LTD. 1-1, NO.136, Haichuan Road,Jiangbei District, Ningbo,Zhejiang, P.R.China			
Product:	Hybrid inverter			
Ratings & Principle Characteristics:	See appendix of Certificate of Conformity			
Model:	AU3KESL, AU3.6KESL, AU4KESL, AU5KESL			
Brand Name <s>:</s>	Austa			
Product Complies with:	IEC 61727:2004 (Second Edition)			
Certificate Issuing Office Name & Address:	Intertek Testing Services Ltd. Shanghai West Area, 2 nd Floor, No. 707, Zhangyang Road China (Shanghai) Pilot Free Trade Zone, Shanghai, P. R. China			
	Accredited by ACCREDIA in accordance with ISO/IEC 17065:2012			
Test Report No. <s>:</s>	231000762SHA-001			
Additional information in Appendix				
\wedge				

Signature

Certification Manager: Qiao Qiao Date: 22 November 2023



PRD Nº 306B

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-230654

Ratings & Principle Characteristics:

Specifications table						
Model	AU3KESL	AU3.6KESL	AU4KESL	AU5KESL		
PV input						
Vmax PV (Vdc) (absolute Max.)		500				
Isc PV (absolute Max.) (A)	22.5	22.5*2	22.5*2	22.5*2		
Max. PV input current / strings (A)	18	18*2	18*2	18*2		
Number MPP trackers	1	2	2	2		
Number input strings	1	1/1	1/1	1/1		
PV Input voltage range (Vdc)	100~500					
MPPT Range (Vdc)	150~450					
Vdc range @ full power (Vdc)	240~425	240~425	240~425	240~425		
Battery (charge/discharge)						
Battery type	Li-ion/Lead-acid					
Battery Normal Voltage (Range) (Vdc)	48V (40-60V)					
Max charge/discharge Current(A)	75	90	100	120		
Max charge/discharge Power(kW)	3.3	3.96	4.4	5.5		
AC Grid (input and output)						
Normal AC Voltage (VAC)	230(single phase)					
Frequency (Hz)	50					
Max. cont. input/output current (A)	15	18	20	25		
Max. cont. input/output Power (kW)	3.3	3.96	4.4	5.5		
Max. cont. Apparent Power (kVA)	3.3	3.96	4.4	5.5		
Power factor(adjustable)	1.0(-0.8~ +0.8)					
AC Load output (stand alone)						
Normal Voltage (VAC)		230(sing	le phase)			
Frequency (Hz)		50				
Nominal Current(A)	15	18	20	25		
Max. cont. Power (kW)	3	3.6	4	5		
Overload Capability (off grid)	>200% for 15 sec					
Output Power Factor(off grid)	1.0					
Output Current Harmonic Distortion	THD<3%(Nonlinear load); THD<1.5%(Linear load)					
Others		· · · · · · · · ·	· · · · ·	ł		
Ingress protection (IP)	IP66					
Protective class	Class I					
Temperature (°C)	-25°C to +60°C (Derating 45°C)					
Inverter Isolation	⊠Non-isolated PV- AC ☐High frequency isolated(Battery Side)					
Overvoltage category	OVC III (AC Main), OVC II (PV)					
Dimensions, D*W*H (mm)	198*427*554	198*427*554	198*427*554	198*427*554		
Weight (kg)	20	20	20	20		

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.